ROYAL ENFIELD

HIMALAYAN

SPECIFICATIONS



ROYAL ENFIELD

ENGINE

Type Liquid cooled, single cylinder, DOHC, 4 valves Bore x Stroke (in mm) 84 mm x 81.5 mm Displacement 451.65cc **Compression Ratio** 11.5:1 Maximum Power 40.02 PS (29.44 kW) @8000 rpm Maximum Torque 40 Nm @5500 rpm Idle RPM 1300 Electric start Starting system Lubrication Semi-dry sump **Engine Oil Grade** 10W40 API SN, JASO MA2, Semi Synthetic Clutch Wet multiplate, slip & assist Gearbox 6 speed **Fuel Injection** Electronic fuel injection, 42mm throttle body, ride by wire system 3.59 l/100km **Fuel Consumption** Co2 Emissions 86.80 g/km Pass By Noise (drive by) 77 dB(A) Stationary Noise 91.51 dB(A) @4065rpm

DIMENSIONS & WEIGHTS

Wheelbase 1510mm **Ground Clearance** 230 mm 2285mm Length Width 852mm Height 1316mm Seat Height 825 mm (Standard Seat adjustable to 845 mm) 805 mm (Low Seat adjustable to 825 mm) Dry Weight 181 kg Kerb Weight (90% Fuel + Oil) 196 kg Payload with Standard Equipment 198 kg **Fuel Capacity** 17.0 Litres

COLOURS













Kamet White

Kaza Brown

Slate Pop

Slate Poppy Blue Sl

Slate Himalayan Salt

Hanle Black

- **CHASSIS & SUSPENSION**
- Type Front Suspension Front Wheel Travel Rear Suspension Rear Wheel Travel
- Steel, twin spar tubular frame Upside down fork, 43mm 200mm Linkage type mono-shock 200 mm

90/90-21"

140/80 R 17"

double piston caliper

single piston caliper

BRAKES & TYRES

Tyres Fr. Tyres Rr. Brakes Front

Brakes Rear

ABS

ELECTRICALS

Electrical System Battery Head Lamp Tail Lamp/ Turn Signal Lamp Other Equipment Cluster 12V 12 V, 8 Ah LED Headlamp Integrated turn & tail Lamp, all LED

Dual Channel ABS, switchable

Hydraulic disc brake, 320mm ventilated disc,

Hydraulic disc brake 270mm Ventilated disc,

Ride modes, USB type C charging point 4 inch round TFT display with phone connectivity, Full Map Navigation (powered by Google Maps), Media controls

