

ENGINE & TRANSMISSION	
PARAMETERS	ROW
Engine Type	Inline twin cylinder, 4 stroke, SOHC
Displacement	648cc
Compression ratio	9.5:1
Max power	47.4 PS (34.9 kW) @ 7150 rpm
Max torque	56.5 Nm @ 5150 rpm
Idle RPM	1200 ± 100 rpm
Ignition	Digital spark ignition
Lubrication	Forced lubrication, Wet sump with pump driven oil delivery
Engine Oil	10W-50 to API SL (or higher) JASO MA2, (Fully synthetic)
Clutch	Wet multi plate
Gear box	6 Speed constant mesh

CHASSIS & SUSPENSION	
PARAMETERS	ROW
Frame	Steel tubular, double cradle frame
Front Suspension	Upside down telescopic fork 43mm
Front wheel travel	130mm
Rear Suspension	Twin shock
Rear wheel travel	115mm
Rake Angle	26.1 deg unladen
Trail	116.7 mm

DIMENSIONS & WEIGHTS	
PARAMETERS	ROW
Wheel Base	1460
Ground Clearance	184
Length	2216mm
Width	855
Height	1160
Kerb Weight (90% Fuel and oil)	214 kg
Gross vehicle weight	400 kg
Fuel tank capacity	13.7 L

BRAKES & TYRES		
PARAMETERS	ROW	
Brake System	Dual Channel ABS, Switchable off at rear	
Front	Hydraulic Disc Brake, Single 320mm Ventilated disc, twin piston floating caliper	
Rear	Hydraulic Disc Brake, Single 270mm Ventilated disc, single piston floating caliper	
Front Tyre (Spoked Wheel)	100/90-19 M/C 57H MRF NYLOREX-F	
Rear Front Tyre (Spoked Wheel)	140/80R17 M/C 69H MRF NYLOREX-X	
TYRE PRESSURE		
PARAMETERS	SOLO	WITH PILLION
Front	32 psi	32 psi
Rear	36 psi	42 psi
ELECTRICALS		
PARAMETERS	ROW	
System	12V - DC	
Battery	12V - 12 Ah VRLA	
Head Lamp	LEAD Headlamp	
Tail lamp & BRAKE LAMP	LED	
License plate illuminator	LED	
Turn Signals	LED - Front & Rear	
Instrument Cluster	Tripper Dash - 4 Inch round TFT Display with phone connectivity, Full Map Navigation (Powered by Google Maps), Media Controls	
Charger port	USB 2.0 Type C 5 V 2 A output	
ENGINE OIL		
PARAMETERS	ROW	
Engine Oil	10W-50 to API AL (or higher) JASO MA2, (Fully synthetic)	
Capacity	1st Dry fill - 3.9 L Refill - 3.1 L	