

BULLET 350

SPECIFICATIONS



ENGINE

Type	Single cylinder, 4 stroke, Air-Oil cooled
Displacement	349cc
Bore x stroke	72 mm x 85.8 mm
Compression Ratio	9.5 : 1
Maximum Power	20.2 BHP @ 6100 rpm (14.87 kW)
Maximum Torque	27 Nm @ 4000 rpm
Ignition System	Electronic Fuel Injection(EFI)
Clutch	Wet, multi-plate
Gearbox	5 Speed constant mesh
Lubrication	Wet sump, forced lubrication
Engine Oil	SAE 15 W 50 API, SL grade, JASO MA 2 Semi Synthetic
Fuel Supply	Electronic Fuel Injection
Air Cleaner	Paper element
Engine Start	Electric
CO2 emissions	67.67 g/km
Noise emissions	89dB(A) at 3050 rpm
Pass by	76.1 dB(A)
Fuel economy	2.63 l/100km

TRANSMISSION

Clutch	Wet multi plate
Primary drive	Gear
Primary ratio	2.313:1
Gear box	Constant mesh
Gear ratio	1st 2.615 :1 2nd 1.706:1 3rd 1.300:1 4th 1.040:1 5th 0.875:1
Secondary drive	Chain
Secondary ratio	2.800:1
Drive Chain Links	104

CHASSIS & SUSPENSION

Type	Twin Downtube Spine Frame
Front suspension	Telescopic, 41mm forks, 130mm travel
Rear suspension	Twin tube Emulsion shock absorbers with 6-step adjustable preload

DIMENSIONS

Wheelbase	1390 mm
Ground Clearance	170 mm
Length	2110
Width	785 mm (without mirrors)
Height	1225 mm (without mirrors)
Seat Height *	805 mm
Kerb Weight	195kg
Fuel Capacity	13 ltr

BRAKES & TYRES

Tyres Fr.	Spokes Wheel - 100/90 - 19" - 57P (Tube Type)
Tyres Rr.	Spokes Wheel - 120/80 - 18" - 62P (Tube Type)
Tyre Pressure	Solo
Front	32 psi
Rear	32 psi
Brakes Front	300 mm disc with twin piston floating caliper
Brakes Rear	270 mm disc, single piston floating caliper
ABS	Dual Channel

ELECTRICALS

Electrical System	12 volt - DC
Battery	12 volt, 8 Ah, VRLA (maintenance free)
Head Lamp	12V, H4-60/55W (Halogen)
Tail Lamp	12V, P21/5W
Turn Signal Lamp	12V, 10W X 2 nos

COLOURS



Black Gold



Standard Black

