

ENGINE

ENGINE	
Туре	Inline twin cylinder, 4 stroke, SOHC
Bore x Stroke (in mm)	78 mm x 67.8 mm
Displacement	647.95 cc
Compression Ratio	9.5:1
Maximum Power	34.6 kW @ 7250 rpm
Maximum Torque	52.3 Nm @ 5650 rpm
Idle RPM	1200 ± 100 rpm
Starting system	Electric start
Lubrication	Forced lubrication, Wetsump with pump driven oil delivery
Engine Oil Grade	Fully synthetic 10W-50 to API SL (or higher) JASO MA2
Clutch	Wet multi plate
Gearbox	6 Speed constant mesh
Fuel Supply	Fuel Injection
Fuel consumption	4.66l/100 km
Co2	104.53 g/km
Stationary noise	86 dB(A)@3575 rpm
Stationary noise CHASSIS & SUSPENSION	86 dB(A)@3575 rpm
	86 dB(A)@3575 rpm Steel Tubular Spine Frame
CHASSIS & SUSPENSION	
CHASSIS & SUSPENSION Type	Steel Tubular Spine Frame
CHASSIS & SUSPENSION Type Front suspension	Steel Tubular Spine Frame Telescopic Fork 43 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel	Steel Tubular Spine Frame Telescopic Fork 43 mm 120 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension	Steel Tubular Spine Frame Telescopic Fork 43 mm 120 mm Twin Shock
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel	Steel Tubular Spine Frame Telescopic Fork 43 mm 120 mm Twin Shock
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel DIMENSIONS	Steel Tubular Spine Frame Telescopic Fork 43 mm 120 mm Twin Shock 90 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel DIMENSIONS Wheelbase	Steel Tubular Spine Frame Telescopic Fork 43 mm 120 mm Twin Shock 90 mm 1475 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel DIMENSIONS Wheelbase Ground Clearance	Steel Tubular Spine Frame Telescopic Fork 43 mm 120 mm Twin Shock 90 mm 1475 mm 154 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel DIMENSIONS Wheelbase Ground Clearance Length	Steel Tubular Spine FrameTelescopic Fork 43 mm120 mm120 mmTwin Shock90 mm1475 mm154 mm2318 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel DIMENSIONS Wheelbase Ground Clearance Length Width	Steel Tubular Spine FrameTelescopic Fork 43 mm120 mm120 mmTwin Shock90 mm1475 mm154 mm2318 mm892 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel DIMENSIONS Wheelbase Ground Clearance Length Width Height	Steel Tubular Spine FrameTelescopic Fork 43 mm120 mm120 mmTwin Shock90 mm1475 mm154 mm2318 mm892 mm1137 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel DIMENSIONS Wheelbase Ground Clearance Length Width Height Seat Height	Steel Tubular Spine Frame Telescopic Fork 43 mm 120 mm 120 mm Twin Shock 90 mm 1475 mm 154 mm 2318 mm 892 mm 1137 mm 800 mm
CHASSIS & SUSPENSION Type Front suspension Front Wheel Travel Rear suspension Rear Wheel Travel DIMENSIONS Wheelbase Ground Clearance Length Width Height Seat Height	Steel Tubular Spine Frame Telescopic Fork 43 mm 120 mm 120 mm Twin Shock 90 mm 1475 mm 154 mm 2318 mm 892 mm 1137 mm 800 mm 407 kg

BRAKES & TYRES

Tyres Fr.	100/90-19"
Tyres Rr.	140/70 R18
Brakes Front	Hydraulic Disc Brake Single 320 mm disc, twin piston floating caliper
Brakes Rear	Hydraulic Disc Brake Single 300 mm disc, twin piston floating caliper
ABS	Dual Channel
ELECTRICALS	
Electrical System	12V
Battery	12V, 12 Ah
Head Lamp	12V, LED Headlamp
Tail Lamp	12V, LED lamp
Turn Signal Lamp	12V, 10 watts
Other Equipment	USB typeC charging point