

CLASSIC 650

SPECIFICATIONS



ENGINE

Type	Inline twin cylinder, 4 stroke, SOHC
Bore x Stroke (in inches)	3.07"x 2.66"
Displacement (in cubic inches)	647.95 cc
Compression Ratio	9.5:1
Maximum Power	47 bhp @ 7150rpm
Maximum Torque	38 lb-ft @ 5250rpm
Idle RPM	1200 ± 100 rpm
Starting system	Electric start
Lubrication	Forced lubrication, Wetsump with pump driven oil delivery
Engine Oil Grade	Fully synthetic 10W-50 to API SL (or higher) JASO MA2
Clutch	Wet multi plate
Gearbox	6 Speed constant mesh
Fuel Supply	Fuel Injection

DIMENSIONS

Wheelbase	58.07"
Ground Clearance	6.06"
Length	30"
Width	35.12"
Height	44.76"
Seat Height	31.50"
Max GVW	897 lbs
Curb Weight (90% Fuel + Oil)	535 lbs
Fuel Capacity	3.9 gal

CHASSIS & SUSPENSION

Type	Steel Tubular Spine Frame
Front suspension	Telescopic Fork 43 mm
Front Wheel Travel	4.72"
Rear suspension	Twin Shock
Rear Wheel Travel	3.54"

BRAKES & TIRES

Tires Fr.	100/90-19
Tires Rr.	140/70 R18
Brakes Front	Hydraulic Disc Brake Single 320 mm disc, twin piston floating caliper
Brakes Rear	Hydraulic Disc Brake Single 300 mm disc, twin piston floating caliper
ABS	Dual Channel

ELECTRICALS

Electrical System	12V
Battery	12V, 12 Ah
Head Lamp	12V, LED Headlamp
Tail Lamp	12V, LED lamp
Turn Signal Lamp	12V, 10 watts
Other Equipment	USB type C charging point

COLOURS



TEAL



Vallam red



CHROME BLACK

