



SPECIFICATIONS



Frame

Frame type Twin Downtube Spine Frame

Dimensions

Weight in running order (Kg.) 181
 Wheelbase (mm) 1370
 Seat height (mm) 790
 Ground clearance (mm) 150.5
 Length x width x height (mm) 2055 x 763 x 1055

Engine

Number of cylinders 1
 Bore x stroke (mm) 75 x 85.5
 Cooling System Air-Oil Cooled
 Displacement (cc) 349
 Injection system ECU controlled
 Valve gear / valves per cylinder 2
 Compression ratio 9.5:1
 Maximum power (kw) 14.87kw@6100 rpm
 Maximum speed (km/h) 114 km/h
 Maximum torque (Nm/rpm) 27Nm@4000 rpm
 CO2 emission (g/km) 64.87
 Idle rpm 1050+100
 Noise Emission 76.1 dB(A) @ 3050 rpm
 Clutch Wet Multiplate
 Secondary transmission Chain
 Gearbox 5 Speed Constant Mesh
 Starting System Electric
 Engine Oil SAE 15W50 API SL Jaso
 MA2 Semi-synthetic

Chassis and Brakes

Front wheel Alloy Wheel - 110/70 - 17" -
 54P (Tubeless)
 Rear wheel Alloy Wheel - 140/70 - 17" -
 66P (Tubeless)
 Front suspension Telescopic, 41mm forks - 130mm travel
 Rear suspension Twin tube Emulsion shock absorbers
 with 6-step adjustable preload. Travel 102mm
 ABS Dual Channel
 Front brake 300mm disc with twin piston floating caliper
 Rear brake 270mm disc, single piston floating caliper

Capacity

Petrol tank (Litres) 13 ± 0.5 litres
 Low fuel warning 4+0.5
 Consumption 2.65 L/100 km

Equipment

Instrument Cluster Digital LCD with analog speedometer
 Emergency stop switch Yes
 Central and side stand Fabricated and Spring loaded
 System Voltage 12v
 Side stand switch Yes

COLOURS



DAPPER ORANGE



DAPPER GREY



DAPPER GREEN



REBEL BLUE