

KEEP HUNTING



ROYAL ENFIELD  
**HUNTR 350**  
SINCE 1901

# SPECIFICATIONS

## ENGINE

TYPE	SINGLE CYLINDER, 4 STROKE, AIR-OIL COOLED
DISPLACEMENT	349CC
BORE X STROKE	72 MM X 85.8 MM
COMPRESSION RATIO	9.5 : 1
MAXIMUM POWER	20.2 BHP @ 6100 RPM (14.87 KW)
MAXIMUM TORQUE	27 NM @ 4000 RPM
IGNITION SYSTEM	ELECTRONIC FUEL INJECTION (EFI) (CONTI)
CLUTCH	WET, MULTI-PLATE
GEARBOX	5 SPEED CONSTANT MESH
LUBRICATION	WET SUMP, FORCED LUBRICATION
ENGINE OIL	SAE 15 W 50 API, SL GRADE, JASO MA 2 SEMI SYNTHETIC
AIR CLEANER	PAPER ELEMENT
ENGINE START	ELECTRIC

## CHASSIS AND SUSPENSION

TYPE	TWIN DOWNTUBE SPINE FRAME
FRONT SUSPENSION	TELESCOPIC, 41MM FORKS
REAR SUSPENSION	TWIN SHOCK ABSORBERS, WITH 6-STEP ADJUSTABLE PRELOAD

## DIMENSIONS

WHEELBASE	1370 MM
GROUND CLEARANCE	160 MM
LENGTH	2055 MM
WIDTH	810 MM (WITHOUT MIRRORS)
HEIGHT	1070 MM (WITHOUT MIRRORS)
SEAT HEIGHT *	790 MM
KERB WEIGHT	181 KG (WITH 90% FUEL & OIL)
FUEL CAPACITY	13 LTR

## BRAKES AND TYRES

TYRES FR.	ALLOY WHEEL- 110/70-17" 54P (TUBLESS TYRE)
TYRES RR.	ALLOY WHEEL - 140/70 - 17" 66P (TUBELESS TYPE)
BRAKES FRONT	300 MM DISC WITH TWIN PISTON FLOATING CALIPER
BRAKES REAR	270 MM DISC, SINGLE PISTON FLOATING CALIPER
ABS	DUAL CHANNEL ABS

## ELECTRICALS

ELECTRICAL SYSTEM	12 VOLT - DC
BATTERY	12 VOLT, 8 AH, VRLA (MAINTENANCE FREE)
HEAD LAMP	HB/LB : 12V, 16.5W/11W (LED) WITH INTEGRATED FPL 12V, 1.65W(LED)
TAIL LAMP	TAIL/STOP : 13.5V, 0.5W/4.8W (LED)
TURN SIGNAL LAMP	12V, 10W X 2 PAIRS [FRONT & REAR]
CLUSTER	DIGI-ANALOG (KMPH)(SINGLE SCALE)
USB CHARGER	USB CHARGER - TYPE-C FAST CHARGING

**KEEP HUNTING**

**ROYAL ENFIELD**

**HNTR 350**

**SINCE 1901**

Some of the components and accessories featured in the photographs may not be a part of the standard fitment and applicable for all markets. For any queries, email us at [support@royalenfield.com](mailto:support@royalenfield.com)



Royal Enfield



Royal Enfield



Royal Enfield