ROYALENFIELD.COM



# SPECIFICATIONS

# **TOP AND MID**

### **ENGINE**

TYPE SINGLE CYLINDER, 4 STROKE, AIR-OIL COOLED

DISPLACEMENT 349CC

BORE X STROKE 72 MM X 85.8 MM

COMPRESSION RATIO 9.5:1

MAXIMUM POWER 20.2 BHP @ 6100 RPM (14.87 KW)

MAXIMUM TORQUE 27 NM @ 4000 RPM

IGNITION SYSTEM ELECTRONIC FUEL INJECTION (EFI) (CONTI)

CLUTCH WET, MULTI-PLATE
GEARBOX 5 SPEED CONSTANT MESH
LUBRICATION WET SUMP, FORCED LUBRICATION

ENGINE OIL SAE 15 W 50 API, SL GRADE, JASO MA 2 SEMI SYNTHETIC

AIR CLEANER PAPER ELEMENT ENGINE START ELECTRIC

### **CHASSIS AND SUSPENSION**

TYPE TWIN DOWNTUBE SPINE FRAME FRONT SUSPENSION TELESCOPIC, 4IMM FORKS REAR SUSPENSION TWIN SHOCK ABSORBERS,

WITH 6-STEP ADJUSTABLE PRELOAD

# **DIMENSIONS**

WHEELBASE 1370 MM
GROUND CLEARANCE 160 MM
LENGTH 2055 MM

WIDTH 810 MM (WITHOUT MIRRORS)
HEIGHT 1070 MM (WITHOUT MIRRORS)

SEAT HEIGHT \* 790 MM

KERB WEIGHT 181 KG (WITH 90% FUEL & OIL)

FUEL CAPACITY 13 LTR

### **BRAKES AND TYRES**

TYRES FR.

ALLOY WHEEL- IIO/70-I7" 54P (TUBLESS TYRE)

TYRES RR.

ALLOY WHEEL - I4O/70 - I7" 66P (TUBELESS TYPE)

BRAKES FRONT

300 MM DISC WITH TWIN PISTON FLOATING CALIPER

BRAKES REAR

270 MM DISC, SINGLE PISTON FLOATING CALIPER

ABS DUAL CHANNEL ABS

## **ELECTRICALS**

ELECTRICAL SYSTEM 12 VOLT - DC

BATTERY 12 VOLT, 8 AH, VRLA (MAINTENANCE FREE)

HEAD LAMP

HB/LB: 12V, 16.5W/IIW (LED) WITH INTEGRATED FPL 12V, 1.65W(LED)

TAIL LAMP

TAIL/STOP: 13.5V, 0.5W/4.8W (LED)

TURN SIGNAL LAMP

12V, 10W X 2 PAIRS [FRONT & REAR]

CLUSTER

DIGI-ANALOG (KMPH) (SINGLE SCALE)

USB CHARGER - TYPE-C FAST CHARGING

# JUNTING 11/// ROYAL ENFIELD

Some of the components and accessories featured in the photographs may not be a part of the standard fitment and applicable for all markets. For any queries, call us at 18002100007 or email us at support@royalenfield.com





Royal Enfield Royal Enfield

