



KEEP HUNTING

ROYAL ENFIELD
HUNTER
350

SPECIFICATIONS

TOP AND MID

ENGINE

TYPE	SINGLE CYLINDER, 4 STROKE, AIR-OIL COOLED
DISPLACEMENT	349CC
BORE X STROKE	72 MM X 85.8 MM
COMPRESSION RATIO	9.5 : 1
MAXIMUM POWER	20.2 BHP @ 6100 RPM (14.87 KW)
MAXIMUM TORQUE	27 NM @ 4000 RPM
IGNITION SYSTEM	ELECTRONIC FUEL INJECTION (EFI) (CONTI)
CLUTCH	WET, MULTI-PLATE
GEARBOX	5 SPEED CONSTANT MESH
LUBRICATION	WET SUMP, FORCED LUBRICATION
ENGINE OIL	SAE 15 W 50 API, SL GRADE, JASO MA 2 SEMI SYNTHETIC
AIR CLEANER	PAPER ELEMENT
ENGINE START	ELECTRIC

CHASSIS AND SUSPENSION

TYPE	TWIN DOWNTUBE SPINE FRAME
FRONT SUSPENSION	TELESCOPIC, 41MM FORKS
REAR SUSPENSION	TWIN SHOCK ABSORBERS, WITH 6-STEP ADJUSTABLE PRELOAD

DIMENSIONS

WHEELBASE	1370 MM
GROUND CLEARANCE	160 MM
LENGTH	2055 MM
WIDTH	810 MM (WITHOUT MIRRORS)
HEIGHT	1070 MM (WITHOUT MIRRORS)
SEAT HEIGHT *	790 MM
KERB WEIGHT	181 KG (WITH 90% FUEL & OIL)
FUEL CAPACITY	13 LTR

BRAKES AND TYRES

TYRES FR.	ALLOY WHEEL- 110/70-17” 54P (TUBLESS TYRE)
TYRES RR.	ALLOY WHEEL - 140/70 - 17” 66P (TUBELESS TYPE)
BRAKES FRONT	300 MM DISC WITH TWIN PISTON FLOATING CALIPER
BRAKES REAR	270 MM DISC, SINGLE PISTON FLOATING CALIPER
ABS	DUAL CHANNEL ABS

ELECTRICALS

ELECTRICAL SYSTEM	12 VOLT - DC
BATTERY	12 VOLT, 8 AH, VRLA (MAINTENANCE FREE)
HEAD LAMP	HB/LB : 12V, 16.5W/11W (LED) WITH INTEGRATED FPL 12V, 1.65W(LED)
TAIL LAMP	TAIL/STOP : 13.5V, 0.5W/4.8W (LED)
TURN SIGNAL LAMP	12V, 10W X 2 PAIRS [FRONT & REAR]
CLUSTER	DIGI-ANALOG (KMPH) (SINGLE SCALE)
USB CHARGER	USB CHARGER - TYPE-C FAST CHARGING

KEEP HUNTING

ROYAL ENFIELD
HUNTER
350

Some of the components and accessories featured in the photographs may not be a part of the standard fitment and applicable for all markets.
For any queries, call us at 18002100007 or email us at support@royalenfield.com



Royal Enfield



Royal Enfield



Royal Enfield