## INTERCEPTOR 650

**SPECIFICATIONS** 



## ROYAL ENFIELD

**ENGINE** 

Gear box

Fuel supply

Type Inline twin cylinder, 4 stroke / SOHC

Bore 78 mm
Stroke 67.8 mm
Capacity 647.95 cc
Compression ratio 9.5:1

 $\begin{array}{ll} \text{Max Power} & 34.9 \, \text{kW} @ \, 7250 \, \text{rpm} \\ \text{Max Torque} & 52.3 \, \text{Nm} @ \, 5150 \, \text{rpm} \\ \text{Idle rpm} & 1200 \pm 100 \, \text{rpm} \\ \text{Starting} & \text{Electric start} \\ \text{Air filter element} & \text{Paper element} \end{array}$ 

Lubrication Forced lubrication, Wet sump with

pump driven oil delivery 6 Speed constant mesh

Valve gear / valves per cylinder Inlet : 4 Valves (2 per Cylinder)

Exhaust: 4 Valves (2 per Cylinder)
Fuel injection
Air cooling

Cooling Air cooling CO2 emissions (g/km) 99.0 (g/km)

Noise emissions 89.0 dB (A) @ 3575 rpm

Engine Oil Fully Synthetic 10W-50 to API SL

(or higher) JASAO MA2,

such as ELF MOTO4 TECH 10W 50

Fuel Consumption 4.21 L/100 km

Fuel Type Unleaded Petrol / E10 or less

**TRANSMISSION** 

Clutch Wet multi plate

Primary drive Gear Primary ratio 2.051:1

Gear box 6 Speed, Constant mesh

Gear ratio, 1st2.615:12nd1.813:13rd1.429:14th1.190:15th1.040:16th0.962:1

Secondary drive Sprockets and chain (5/8 Pitch)

Secondary ratio 2.533:1

**CHASSIS AND BRAKES** 

Frame Steel tubular, double cradle frame

Front Brake 320 mm disc, ABS Rear Brake 240 mm disc, ABS ABS Dual channel ABS
Tires Front 100/90-18 M/C 56H
Rear Tire 130/70-R18 M/C 63V /

130/70-18 M/C 63H Front Suspension Telescopic forks

Rear Suspension Twin gas charged shock-absorbers

with adjustable preload

**DIMENSIONS** 

Rake 24 degrees

(Alloy & Spokes wheel) 18 M/C x MT 2.50

Rear wheel rim size

Front wheel rim size

(Alloy & Spokes wheel) 18 M/C x MT 3.50

Length 2119 mm Width 835 mm Height 1067 mm **Seat Height** 805 mm Wheelbase 1398 mm **Ground clearance** 174 mm 217 kg Kerb weight **Gross Vehicle Weight** 400 kg Tank capacity 13.7 L

**IGNITION** 

Ignition Digital spark ignition

Ignition advanced 11.25°BTDC
Spark plug BOSCH UR5CC
Spark plug gap 0.7 mm to 0.8 mm

**ELECTRICALS** 

Electrical System 12V - DC

Battery 12V - 12 Ah VRLA

Head lamp Front Position Lamp 1.55 W LED,

low beam 12.1 W, high beam + low beam 14.2 W

Brake/ Tail lamp 12 V, P21/5 W (Halogen)

Turn signal lamp 12 V, 10 W Charger USB Hazard signal Yes







## **COLOURS**





Mark 2 — Sunset Strip