

TECHNICAL SPECIFICATION

ENGINE

Type	Single cylinder, 4 stroke, Air-Oil cooled
Displacement	349.34 cc
Bore x stroke	72 mm x 85.8 mm
Compression Ratio	9.5 : 1
Maximum Power	20.2 BHP @ 6100 rpm (14.87 kW)
Maximum Torque	27 Nm @ 4000 rpm
Ignition System	Electronic Fuel Injection(EFI)
Clutch	Wet, multi-plate
Gearbox	5 Speed constant mesh
Lubrication	Wet sump, forced lubrication
Engine Oil	SAE 15 W 50 API, SL grade, JASO MA 2 Semi Synthetic
Fuel Supply	Electronic Fuel Injection
Air Cleaner	Paper element
Engine Start	Electric

CHASSIS & SUSPENSION

Type	Twin Downtube Spine Frame
Front suspension	Telescopic, 41mm forks, 130mm travel
Rear suspension	Twin tube Emulsion shock absorbers with 6-step adjustable preload

DIMENSIONS

Wheelbase	1400 mm
Ground Clearance	170 mm
Length	2140 mm
Width	845 mm (without mirrors)
Height	1140 mm (without mirrors) 1310 mm (with Windscreen)
Seat Height	765 mm
Kerb Weight	191 kg (with 90% fuel & oil)
Fuel Capacity	15 ltr

*The specifications of the motorcycle may vary as per the variant.

TECHNICAL SPECIFICATION

BRAKES & TYRES

Tyres Fr.	Spokes Wheel / Alloy Wheel - 100/90 - 19" - 57P (Tubeless Type)
Tyres Rr.	Spokes Wheel / Alloy Wheel - 140/70 - 17 - 66P (Tubeless Type)
Brakes Front	300 mm disc with twin piston floating caliper
Brakes Rear	270 mm disc, single piston floating caliper
ABS	Dual Channel

ELECTRICALS

Electrical System	12 volt - DC
Battery	12 volt, 8 Ah, VRLA (maintenance free)
Head Lamp	12 V LED, 22.5 W / 15.6 W
Tail Lamp	12V, LED type - 2.4/1.2W
Turn Signal Lamp	12 V LED, 1.7 W * 2 nos

*The specifications of the motorcycle may vary as per the variant.