SCRAM 440 - NEPAL	
ENGINE	
Туре	Single cylinder, 4 stroke, SOHC, air-cooled, fuel
	injection
Bore x Stroke ( in mm)	81 x 86 mm
Displacement	443 CC
Compression Ratio	9.5:1
Maximum Power	25.4 Bhp (18.7 KW) @ 6250 rpm
Maximum Torque	34 Nm @ 4000 rpm
Idle RPM	1300 rpm
Starting system	Electric Start
Lubrication	Wet Sump
Engine Oil Grade	SEMI SYNTHETIC SAE 15W 50 API SL
	GRADE JASO MA 2
Clutch	Wet Multi Plates
Gearbox	6 Speed
Fuel injection	Electronic Fuel Injection
CHASSIS & SUSPENSION	
Туре	HALF-DUPLEX SPLIT CRADLE FRAME
Front suspension	Telescopic, 41mm forks
Front Wheel Travel	190 mm travel
Rear suspension	Monoshock with linkage
Rear Wheel Travel	180 mm wheel travel
DIMENSIONS & WEIGHTS	
Wheelbase	1460mm
Ground Clearance	200mm
Length	2165mm
Width	840mm
Height	1170mm (without mirrors)
Seat Height	795 mm
Dry Weight	187 Kg (Alloy / Spoke)
Kerb Weight (90% Fuel + Oil)	196 Kg (Alloy / Spoke)
Payload with Standard Equipment	179 Kg
Fuel Capacity	15 L

## **BRAKES & TYRES** Wheel Type Spoke/Alloys Tube/ Tubeless Tyre Type 100/90 - 19" - dual-purpose tyres Tyres Fr. 120/90 - 17" - dual purpose tyres Tyres Rr. Hydraulic Disc Brake 300mm disc, 2-piston floating **Brakes Front** caliper Hydraulic Disc Brake240 mm disc, single piston floating **Brakes Rear** caliper ABS Dual Channel, Swichtable at rear **ELECTRICALS Electrical System** 12 V **Battery** 12 V, 8 Ah Maintenance Free **Head Lamp** 14/12W LED **LED** Tail Lamp **Turn Signal Lamp** 12V, 10W Other Equipment USB Charger - Type A Cluster Digital - Analogue cluster **Navigation** Tripper Pod (Optional)

## ROYAL ENFIELD