

BULLET 350 ES

TECHNICAL SPECIFICATIONS



ENGINE

| | |
|-------------------|--|
| Type | Single cylinder 4 stroke, air cooled fuel injection |
| Displacement | 346cc |
| Bore x stroke | 70 mm x 90 mm |
| Compression ratio | 8.5 : 1 |
| Maximum power | 19.1 bhp @ 5250 rpm |
| Maximum torque | 28 Nm @ 4000 rpm |
| Ignition system | Electronic ignition ECU/Variable |
| Clutch | Wet multiplate (6 plates) |
| Gearbox | Constant mesh, 5 speed |
| Lubrication | Wet sump |
| Engine oil | SAE 15W 50 API SL Grade & Above JASO MA2 Semi Synthetic |
| Fuel supply | Electronic fuel injection |
| Air cleaner | Paper element |
| Engine start | Kick Start / E-Start |

BRAKES & TYRES

| | |
|--------------|---|
| Tyres front | 3.25 X 19" - 54P |
| Tyres rear | 3.25 X 19" - 60P |
| Brakes front | 280 mm disc, 2-Piston caliper with ABS |
| Brakes rear | 153 mm Drum, Single Lead Internal Expanding |
| ABS | Single Channel (Front Brake) |

ELECTRICALS

| | |
|-------------------|--------------------------|
| Electrical system | 12 volt - DC |
| Battery | 12 V - 8 Ah VRLA |
| Head lamp | 12V, HSI-35/35 W Halogen |
| Tail lamp | 12V, 21W/5W |
| Turn signal lamp | 12V, 10W X 4 Nos. |

CHASSIS & SUSPENSION

| | |
|------------------|---|
| Type | Single downtube, using engine as stressed member |
| Front suspension | Telescopic, 35 mm forks, 130 mm travel |
| Rear suspension | Twin shock absorbers with 5 step adjustable preload, 80 mm travel |

DIMENSIONS

| | |
|------------------|-------------------------------|
| Wheelbase | 1395 mm |
| Ground clearance | 135 mm |
| Length | 2170 mm |
| Width | 810 mm (without mirrors) |
| Seat Height * | 800 mm |
| Height | 1120 mm (without mirrors) |
| Kerb weight | 191 kgs (with 90% fuel & oil) |
| Fuel capacity | 13.5 ltr |

COLOURS

Seat Height * - Measured Value



Jet Black



Royal Blue



Regal Red