

CLASSIC 350 REDDITCH

TECHNICAL SPECIFICATIONS



*Images are for representational purposes only. Actual product may vary.

ENGINE

Type	Single cylinder, 4 stroke, twinspark, air-cooled
Displacement	346cc
Bore x stroke	70 mm x 90 mm
Compression ratio	8.5 : 1
Maximum power	19.8 bhp @ 5250 rpm
Maximum torque	28 Nm @ 4000 rpm
Ignition system	Transistorised coil Ignition
Clutch	Wet, multi-plate
Gearbox	5 speed constant mesh
Lubrication	Wet sump
Engine oil	15 W 50 API, SL grade & above, JASO MA 2
Fuel supply	29 mm, constant vacuum carburettor
Air cleaner	Paper element
Engine start	Electric/kick

CHASSIS & SUSPENSION

Type	Single downtube, using engine as stressed member
Front suspension	Telescopic, 35 mm forks, 130 mm travel
Rear suspension	Twin gas charged shock absorbers with 5-step adjustable preload, 80 mm travel

DIMENSIONS

Wheelbase	1390 mm
Ground clearance	135 mm
Length	2160 mm
Width	790 mm (without mirrors)
Height	1090 mm (without mirrors)
Fuel capacity	13.5 ltr
Kerb weight	194 kg (with 90% fuel & oil)

BRAKES & TYRES

Tyres front	90/90 - 19
Tyres rear	110/90 - 18
Brakes front	280mm disc, 2-piston caliper
Brakes rear	240mm disc, single piston caliper
ABS	Dual channel

ELECTRICALS

Electrical system	12 volt - DC
Battery	12 volt, 8 Ah
Head lamp	60W / 55W (halogen)
Tail lamp	12V, P21 / 5W
Turn signal lamp	12V, 10W * 4 Nos

COLOURS


Redditch blue



Redditch red



Redditch green