CONTINENTAL GT 650

SPECIFICATIONS



ROYAL ENFIELD

ENGINE

Type Inline twin cylinder, 4 stroke / SOHC

Bore 78 mm
Stroke 67.8 mm
Capacity 647.95 cc
Compression ratio 9.5:1

 $\begin{array}{lll} \text{Max Power} & 34.9 \, \text{kW} @ \, 7250 \, \text{rpm} \\ \text{Max Torque} & 52.3 \, \text{Nm} @ \, 5150 \, \text{rpm} \\ \text{Idle rpm} & 1200 \pm 100 \, \text{rpm} \\ \text{Starting} & \text{Electric start} \\ \text{Air filter element} & \text{Paper element} \end{array}$

Lubrication Forced lubrication, Wet sump with

pump driven oil delivery

Gear box 6 Speed constant mesh

Fuel supply Fuel injection
Cooling Air cooling
CO2 emissions 99.0 (g/km)

Noise emissions 99.0 (g/km)

Noise emissions 89.0 dB (A) @ 3575 rpm

Valve gear / valves per cylinder Inlet: 4 Valves (2 per Cylinder)

Exhaust : 4 Valves (2 per Cylinder)
Engine Oil Fully Synthetic 10W-50 to API SL

(or higher) JASAO MA2,

such as ELF MOTO4 TECH 10W 50

Fuel Consumption 4.21 L/100 km

Fuel Type Unleaded Petrol / E10 or less

TRANSSMISION

Clutch Wet multi plate

Primary drive Gear Primary ratio 2.051:1

Gear box 6 Speed, Constant mesh

Gear ratio, 1st2.615:12nd1.813:13rd1.429:14th1.190:15th1.040:16th0.962:1

Secondary drive Sprockets and chain (5/8 Pitch)

Secondary ratio 2.533:1

CHASSIS AND BRAKES

Frame Steel tubular, double cradle frame

Front Brake 320 mm disc, ABS
Rear Brake 240 mm disc, ABS
ABS Dual channel ABS

Tires Front 100/90-18 M/C 56H Rear Tire 130/70-R18 M/C 63V /

130/70-18 M/C 63H

Front Suspension Telescopic forks

Rear Suspension Twin gas charged shock-absorbers

with adjustable preload

DIMESNSIONS

Rake 24 degrees

Front wheel rim size

(Alloy & Spokes wheel) 18 M/C x MT 2.50

Rear wheel rim size

(Alloy & Spokes wheel) 18 M/C x MT 3.50

Length 2119 mm Width 780 mm Height 1067 mm Seat Height 820 mm Wheelbase 1398 mm **Ground clearance** 174 mm Kerb weight 212 kg **Gross Vehicle Weight** 400 kg Tank capacity 12.5 L

IGNITION

Ignition Digital spark ignition

Ignition advanced 11.25°BTDC
Spark plug BOSCH UR5CC
Spark plug gap 0.7 mm to 0.8 mm

ELECTRICALS

Brake/ Tail lamp

Electrical System 12V - DC

Battery 12V - 12 Ah VRLA

Head lamp Front Position Lamp 1.55 W LED,

low beam 12.1 W, high beam + low beam 14.2 W

12 V, P21/5 W (Halogen)

Turn signal lamp 12 V, 10 W
Charger USB
Hazard signal Yes
Hazard signal Yes







COLOURS











