ROYAL ENFIELD

CLASSIC 350

SPECIFICATIONS

FRAME

Frame type	Twin Downtube Spine Frame

DIMENSIONS

Weight in running order (Kg.)	195
Wheelbase (mm)	1390
Seat height (mm)	805
Ground clearance (mm)	170
Length x width x height (mm)	2145 x 785 x 1090

ENGINE

Number of cylinders	1
Bore x stroke (mm)	72 x 85.8
Cooling System	Air-Oil Cooled
Displacement (cc)	349.34
Injection system	ECU controlled
Valve gear / valves per cylinder	2
Compression ratio	9.5:1
Maximum power (Kw/HP-rpm)	14.87 kW @ 6100 rpm
Maximum speed (mph)	114 km/h (4th Gear)
Maximum torque (Nm/rpm)	27Nm@4000 rpm
CO2 emission (g/km)	63.4
Idle rpm	1050 ± 100 rpm
Noise Emission	89 dB(A) @ 3050 rpm
Clutch	Conventional Wet Clutch
Secondary transmission	Chain
Gearbox	5 Speed Constant Mesh
Starting System	Electric
Engine Oil	SAE 15W50 API SL Jaso MA2 Semi-synthetic

CHASSIS AND BRAKES

Front wheel	Spoke Wheel - 100/90 - 19" - 57P (Tube Type)
Rear wheel	Spoke Wheel - 120/80 - 18" - 62P (Tube Type)
Front suspension	Telescopic, 41mm forks
Rear suspension	Twin tube Emulsion shock absorbers with 6-step adjustable preload
ABS	Dual-Channel
Front brake	300mm disc with twin piston floating caliper
Rear brake	270mm disc, single piston floating caliper

CAPACITY

Petrol tank (imperial gallons)	13 ± 0.5 litres
Low fuel warning	4 ± 0.5 litres
Consumption (mpg)	2.63 L/100 km

EQUIPMENT

Instrument Cluster	Digital LCD with analog speedometer
Emergency stop switch	Yes
Central and side stand	Fabricated and Spring loaded
Tool kit	Provided in Right side cabinet of vehicle
Side stand switch	Yes

COLOURS

Halcyon Black — Halcyon Green — Halcyon Grey — Dark Stealth Black — Dark Gunmetal Grey — Chrome Red — Chrome Bronze — Signals Marsh Grey — Signals SandStorm