

# CLASSIC 350

---

## SPECIFICATIONS



## FRAME

Frame type Twin Downtube Spine Frame

## DIMENSIONS

Weight in running order (Kg.) 195  
 Wheelbase (mm) 1390  
 Seat height (mm) 805  
 Ground clearance (mm) 170  
 Length x width x height (mm) 2145 x 785 x 1090

## ENGINE

Number of cylinders 1  
 Bore x stroke (mm) 72 x 85.8  
 Cooling System Air-Oil Cooled  
 Displacement (cc) 349.34  
 Injection system ECU controlled  
 Valve gear / valves per cylinder 2  
 Compression ratio 9.5:1  
 Maximum power (Kw/HP-rpm) 14.87 kW @ 6100 rpm  
 Maximum speed (mph) 114 km/h (4th Gear)  
 Maximum torque (Nm/rpm) 27Nm@4000 rpm  
 CO2 emission (g/km) 63.4  
 Idle rpm 1050 ± 100 rpm  
 Noise Emission 89 dB(A) @ 3050 rpm  
 Clutch Conventional Wet Clutch  
 Secondary transmission Chain  
 Gearbox 5 Speed Constant Mesh  
 Starting System Electric  
 Engine Oil SAE 15W50 API SL Jaso MA2 Semi-synthetic

## CHASSIS AND BRAKES

Front wheel Spoke Wheel - 100/90 - 19" - 57P (Tube Type)  
 Rear wheel Spoke Wheel - 120/80 - 18" - 62P (Tube Type)  
 Front suspension Telescopic, 41mm forks  
 Rear suspension Twin tube Emulsion shock absorbers with 6-step adjustable preload  
 ABS Dual-Channel  
 Front brake 300mm disc with twin piston floating caliper  
 Rear brake 270mm disc, single piston floating caliper

## CAPACITY

Petrol tank (imperial gallons) 13 ± 0.5 litres  
 Low fuel warning 4 ± 0.5 litres  
 Consumption (mpg) 2.63 L/100 km

## EQUIPMENT

Instrument Cluster Digital LCD with analog speedometer  
 Emergency stop switch Yes  
 Central and side stand Fabricated and Spring loaded  
 Tool kit Provided in Right side cabinet of vehicle  
 Side stand switch Yes

## COLOURS



Halcyon Black



Halcyon Green



Halcyon Grey



Dark Stealth Black



Dark Gunmetal Grey



Chrome Red



Chrome Bronze



Signals Marsh Grey



Signals SandStorm