HIMALAYAN

EURO 5 - SPECIFICATIONS



ROYAL ENFIELD

ENGINE

Number of cylinders Single Cylinder, 4 stroke

Displacement (cc) 411

Bore x stroke 78 x 86 mm

Air cooled with oil cooler **Cooling System** Electronic ECU / Variable **Injection system**

Valve gear / SOHC, Camshaft in cylinder head, 2 valves

valves per cylinder

Compression ratio 9.5:1

17,88 kW / 24.3 bhp @ 6500 rpm Maximum power

(Kw/HP-rpm)

Maximum torque 32 Nm @ 4250 +/- 250 rpm

(Nm/rpm)

CO₂ emission 76.5 g/km

Idle rpm 1250 +/- 100 rpm

88.0 dB(A) @3250rpm **Noise Emission**

Clutch Wet multi plates Secondary transmission Double chain

Gearbox 5 Speed, Constant Mesh

Starting System Electric Start

Engine Oil SAE 15W50 API SL Jaso MA2

Semi-synthetic

DIMENSIONS

LxWxH (mm) 2190 x 840 x 1370

Ground clearance 220 mm Wheelbase 1465 mm 800 mm Seat height Weight in running order 199 kg

CAPACITY

Petrol tank 3.3 +/- 0.11 gallons

(imperial gallons)

Low fuel warning 1.21 +/- 0.11 gallons Consumption 3.18 (L/100Kms)

Unleaded Petrol, E10 or less Fuel

EQUIPMENT

Instrument Cluster Digital cluster with main

and compass LCD

"Tripper" Turn-by-Turn **Navigation**

Emergency stop switch Central and side stand

Engine Guard

Tool kit **Burst switch**

Side stand switch

Luggage rack

PRICING

Granite Black £4.599 **Gravel Grey** £4.599 Mirage Silver £4,699 £4.699 Pine Green Lake Blue £4,699 **Rock Red** £4,699



CHASSIS AND BRAKES

Half duplex split cradle Frame type 90/90-21 M/C 54H Front wheel Rear wheel 120/90-17 64S

Front suspension Hydraulic telescopic fork 41 mm Ø. 200 mm travel

Rear suspension Progressive central spring strut 5-way adjustable, 180mm travel

ABS Dual Channel ABS (Switchable to Single Channel ABS

- Rear Wheel ABS Control Deactivation)

Front brake Disc (300mm), 2-piston floating caliper Rear brake Disc (240mm), 1-piston floating caliper

COLOURS



Granite Black











HIMALAYAN

EURO 4 - SPECIFICATIONS



ROYAL ENFIELD

ENGINE

Type / cooling 1-cylinder 4-stroke inline engine, air-cooled with oil cooler

Capacity 411 cc

Valve gear / valves per cyl. one overhead camshaft, two valves

Power / torque 18 kW / 24 hp at 6500 rpm, 32 Nm at 4500 rpm

Transmission 5 gears

Consumption/

emissions standard 3.01/100 km, Euro 4

CO2 emissions 74 g/km

Noise emissions 88 dB (A) @ 3250 rpm

CHASSIS AND BRAKES

Design type Tubular steel frame with bolted trussing

Wheel travel front / rear 200 mm / 180 mm
Front brake 300 mm disc brake
Rear brake 240 mm disc brake

ABS Bosch M 9.1 ABS dual-channel

Tires front 90 / 90-21 MC 56H Rear tire 120/90-17 MC 64S

DIMENSIONS & WEIGHT

LxWxH (mm) 2190 x 840 x 1360

Ground clearance 220 mm
Wheelbase 1465 mm
Seat height 800 mm
Kerb weight 191 kg
Useful load 174 kg
Tank capacity 15.01

PRICING

Granite	£4,499
Snow	£4,499
Sleet	£4,499
Gravel Grey	£4,599
Lake Blue	£4,599
Rock Red	£4,599





COLOURS













Snow white — Granite black — Sleet grey — Rock red — Lake blue — Gravel grey