METEOR 350



ROYAL ENFIELD

FRAME

DIMENSIONS

Wheelbase (mm)

Seat height (mm)

Ground clearance (mm)

Weight in running order (Kg.)

Length x width x height (mm)

(without mirrors & without

Frame type Twin Downtube Spine Frame

191

1400

765

170

2140 x 845 x 1140

Front wheel Tyre 100/90-19 M/C 57P

CHASSIS AND BRAKES

(For After Market replacemnt - 100/90-19

M/C 57V - Metzler)

Rear wheel Tyre 140/70-17 M/C 66P

(For After Market replacemnt 140/70-17

M/C 66H - Metzler)

Front suspension Telescopic 41 mm Forks, 130mm Travel
Rear suspension Twin Tube Emulsion shock absorber with

6 step adjustable preload

ABS Dual Channel

Front brake 300mm disc with twin piston floating caliper Rear brake 270mm disc, single piston floating caliper

ENGINE

windshield)

Number of cylinders 1

Bore x stroke (mm) 72x85.8

Cooling System Air-Oil Cooled

Displacement (cc) 349

Injection system ECU controlled

Valve gear / valves per cylinder 2 Compression ratio 2 9.5:1

Maximum power (kw/bhp-rpm) 14.87kW@6100 rpm

Maximum speed 114 km/h (4th Gear) (70.8 mph)

Maximum torque (Nm @ rpm) 27Nm@4000 rpm

CO2 emission (g/km) 67.25 g/km Idle rpm 1050 ± 100

Noise Emission (dB-(A) - rpm) 89.0 dB(A) @ 3050 rpm Clutch Conventional Wet Clutch

Secondary transmission Chain

Gearbox 5 Speed Constant Mesh

Starting System Electric

Engine Oil SAE 15W50 API SL Jaso MA2

Semi-synthetic

CAPACITY

Petrol tank (imperial gallons) 3.3 ± 0.11 Low fuel warning 1.1 ± 0.11

Consumption (2.79 L/100 km)

EQUIPMENT

Instrument Cluster Digital LCD with analog speedometer
Navigation Model year 24 -Tripper standard fit

*previous model years - Tripper available

Engine Kill Switch Yes

Head Lamp 12V, 14/12W (LED) - LED head lamp standard fit on

Aurora and Supernova variants only.

Fabricated and Spring loaded

Central and side stand

Engine Guard

Tool kit Provided in Right side cabinet of vehicle

Side stand switch Yes

Luggage rack







COLOURS















