HIMALAYAN



ROYAL ENFIELD

FRAME

Frame type Half duplex split cradle

DIMENSIONS

Weight in running order (Kg.)

Wheelbase (mm)

Seat height (mm)

Ground clearance (mm)

199

800

220

Length x width x height (mm) 2190 X 840 x 1370

ENGINE

Number of cylinders Single Cylinder, 4 stroke

Bore x stroke (mm) 78 x 86

Cooling System Air cooled with oil cooler

Displacement (cc) 411

Injection system Electronic ECU / Variable
Valve gear / valves per cylinder SOHC, Camshaft in cylinder

head, 2 valves

76.5 g/mile

1250 +/- 100 rpm

Wet multi plates

Double chain

Electric Start

Semi-synthetic

88.0 dB(A) @3250rpm

5 Speed, Constant Mesh

SAE 15W50 API SL Jaso MA2

Compression ratio 9.5:1

Maximum power (Kw/HP-rpm) 17,88 kW / 24.3 bhp @ 6500 rpm

Maximum speed (mph) 79

Maximum torque (Nm/rpm) 32 Nm @ 4250 +/- 250 rpm

CO2 emission (g/mile)

Idle rpm

Noise Emission

Clutch

Secondary transmission

Gearbox

Starting System

Engine Oil

CHASSIS AND BRAKES

Front wheel 90/90-21 M/C 54H
Rear wheel 120/90-17 64S

Front suspension hydraulic telescopic fork 41 mm Ø. 200 mm travel
Rear suspension progressive central spring strut 5-way adjustable,

180mm travel

ABS Dual Channel ABS (Switchable to Single Channel ABS -

Rear Wheel ABS Control Deactivation)

Front brake Disc (300mm), 2-piston floating caliper
Rear brake Disc (240mm), 1-piston floating caliper

CAPACITY

Petrol tank 3.3 +/- 0.11 gallons

(imperial gallons)

Low fuel warning 1.21 +/- 0.11 gallons

Consumption (mpg) 88.83

EQUIPMENT

Instrument Cluster

Navigation

Digital cluster with main and compass LCD

Tripper Compatible - accessory fit

(subject to availability)

Emergency stop switch Central and side stand

Engine Guard

Tool kit

Burst switch Side stand switch

Luggage rack

(A2)





COLOURS











