

SPECIFICATIONS

Engine

Type Parallel twin, 4 stroke, SOHC, Air-Oil Cooled

Displacement 648cc

Bore x stroke 78 mm x 67.8 mm

Compression Ratio 9.5:1

Maximum Power 34.6 kW (47PS) @7250 rpm

52.3 Nm @5650 rpm **Maximum Torque** Clutch Wet, multi-plate

6 Speed constant mesh **Gearbox Electronic Fuel Injection Fuel Supply**

Air Cleaner Paper element

Engine Start Electric

Chassis & Suspension

Type Steel Tubular Spine Frame

Front suspension 43mm Upside Down Telescopic Fork, 120mm travel **Rear suspension** Twin Shocks, 101mm travel, preload adjustable

Dimensions

Wheelbase 1500 mm **Ground Clearance** 135 mm Length 2260 mm

Width 890 mm (without mirrors)

Height 1155 mm **Seat Height** 740 mm

241 kg (with 90% fuel & oil) **Kerb Weight**

Fuel Capacity 15.7 litres

Brakes & Tyres

100/90 - 19 M/C 57H (Tubeless Type) Tyres Fr. 150/80 B16 M/C 71H (Tubeless Type) Tyres Rr.

Single 320mm disc, twin piston floating caliper **Brakes Front** Single 300mm disc, twin piston floating caliper **Brakes Rear**

ABS Dual Channel

Electricals



