HIMALAYAN



ROYAL ENFIELD

FRAME

Half duplex split cradle Frame type

DIMENSIONS

Weight in running order (Kg.) 199 Wheelbase (mm) 1465 Seat height (mm) 800 Ground clearance (mm) 220

Length x width x height (mm) 2190 X 840 x 1370

ENGINE

Number of cylinders Single Cylinder, 4 stroke

Bore x stroke (mm) 78 x 86

Cooling System Air cooled with oil cooler

Displacement (cc) 411

Injection system Electronic ECU / Variable

Valve gear / valves per cylinder SOHC, Camshaft in cylinder

head, 2 valves

Compression ratio 9.5:1

Maximum power (kw/rpm) 17,88 kw @ 6500 rpm

Maximum speed (km/h) 79

Maximum torque (Nm/rpm) 32 Nm @ 4250 +/- 250 rpm 76.5 g/km

CO2 emission (g/km)

Idle rpm Noise Emission

Clutch

Secondary transmission

Gearbox

Starting System

Electric Start Engine Oil SAE 15W50 API SL Jaso MA2

Semi-synthetic

1250 +/- 100 rpm

Wet multi plates

Double chain

88.0 dB(A) @3250rpm

5 Speed, Constant Mesh

CHASSIS AND BRAKES

Front wheel 90/90-21 M/C 54H Rear wheel 120/90-17 64S

Front suspension hydraulic telescopic fork 41 mm Ø. 200 mm travel Rear suspension progressive central spring strut 5-way adjustable,

180mm travel

Dual Channel ABS (Switchable to Single Channel ABS -**ABS**

Rear Wheel ABS Control Deactivation)

Front brake Disc (300mm), 2-piston floating caliper Rear brake Disc (240mm), 1-piston floating caliper

CAPACITY

Petrol tank 3.3 +/- 0.11 gallons

(imperial gallons)

Low fuel warning 1.21 +/- 0.11 gallons

88.83 km Consumption

EQUIPMENT

Instrument Cluster

Emergency stop switch Central and side stand

Engine Guard

Tool kit **Burst switch**

Side stand switch

Luggage rack **USB Port**

Digital cluster with main and compass LCD







COLOURS



GRAVEL GREY









