



WHEELIE

READY.

SET.

SCRAM

SPECIFICATIONS

ENGINE

TYPE	SINGLE CYLINDER, 4 STROKE, AIR COOLED, SOHC, FUEL INJECTION
BORE X STROKE	78MM X 86MM
DISPLACEMENT	411 CC
COMPRESSION RATIO	9.5:1
MAXIMUM POWER	24.3BHP(17.88KW)@6500RPM
MAXIMUM TORQUE	32NM@4250±250RPM
IDLE RPM	1300±100RPM
STARTING SYSTEM	ELECTRIC START
AIR FILTER ELEMENT	PAPER ELEMENT
LUBRICATION	FORCED, WET SUMP
ENGINE OIL GRADE	SEMI SYNTHETIC SAE 15W 50 API SL GRADE JASO MA 2
IGNITION SYSTEM	ELECTRONIC ECU / VARIABLE
CLUTCH	WET MULTI PLATES
GEARBOX	5 SPEED, CONSTANT MESH
FUEL SUPPLY	ELECTRONIC FUEL INJECTION

CHASSIS & SUSPENSION

TYPE	HALF-DUPLEX SPLIT CRADLE FRAME
FRONT SUSPENSION	TELESCOPIC, 41 MM FORKS 190MM TRAVEL
REAR SUSPENSION	MONOSHOCK WITH LINKAGE, 180MM WHEEL TRAVEL

DIMENSIONS

WHEELBASE	1455 MM
GROUND CLEARANCE	200 MM
LENGTH	2210 MM
WIDTH	840 MM
HEIGHT	1165 MM
SADDLE HEIGHT	800 MM
KERB WEIGHT (90% FUEL & OIL)	194 KG
FUEL CAPACITY	15 ± 0.5 LITRES

BRAKES & TYRES

TYRES FR.	100/90 -19" 57S
TYRES RR.	120/90 - 17" 64S
BRAKES FRONT	300MM DISC, 2-PISTON FLOATING CALIPER
BRAKES REAR	240MM DISC, SINGLE PISTON FLOATING CALIPER
ABS	DUAL CHANNEL ABS

COLORS



WHITE FLAME



SILVER SPIRIT



GRAPHITE RED



BLAZING BLACK



GRAPHITE BLUE



SKYLINE BLUE



GRAPHITE YELLOW

HERFAS

ROYAL ENFIELD

www.royalenfield.com

On all things Royal Enfield, reach us at www.royalenfield.com

 **ROYALENFIELD**  **@ROYALENFIELD**  **@ROYALENFIELD**