

# CLASSIC 500 STEALTH BLACK

## TECHNICAL SPECIFICATIONS



\*Images are for representational purposes only. Actual product may vary.

**ENGINE**

|                   |                                                                       |
|-------------------|-----------------------------------------------------------------------|
| Type              | Single cylinder, 4 stroke, spark ignition, air-cooled, fuel injection |
| Displacement      | 499cc                                                                 |
| Bore x stroke     | 84mm x 90mm                                                           |
| Compression ratio | 8.5 : 1                                                               |
| Maximum power     | 27.2 bhp @ 5250 rpm                                                   |
| Maximum torque    | 41.3 Nm @ 4000 rpm                                                    |
| Ignition system   | Digital electronic ignition                                           |
| Clutch            | Wet, multi-plate                                                      |
| Gearbox           | 5 speed constant mesh                                                 |
| Lubrication       | Wet sump                                                              |
| Engine oil        | 15 W 50 API, SL grade & above, JASO MA 2                              |
| Fuel supply       | Electronic fuel injection                                             |
| Air cleaner       | Paper element                                                         |
| Engine start      | Electric/kick                                                         |

**CHASSIS & SUSPENSION**

|                  |                                                                               |
|------------------|-------------------------------------------------------------------------------|
| Type             | Single downtube, using engine as stressed member                              |
| Front suspension | Telescopic, 35 mm forks, 130 mm travel                                        |
| Rear suspension  | Twin gas charged shock absorbers with 5-step adjustable preload, 80 mm travel |

**DIMENSIONS**

|                  |                              |
|------------------|------------------------------|
| Wheelbase        | 1380 mm                      |
| Ground clearance | 135 mm                       |
| Length           | 2140 mm                      |
| Width            | 790 mm (without mirrors)     |
| Height           | 1090 mm (without mirrors)    |
| Kerb weight      | 196 kg (with 90% fuel & oil) |
| Fuel capacity    | 13.5 ltr                     |

**BRAKES & TYRES**

|              |                                    |
|--------------|------------------------------------|
| Tyres front  | 90/90 - 19                         |
| Tyres rear   | 120/80 - 18                        |
| Brakes front | 280 mm disc, 2-piston caliper      |
| Brakes rear  | 240 mm disc, single piston caliper |
| ABS          | Dual channel                       |

**ELECTRICALS**

|                   |                           |
|-------------------|---------------------------|
| Electrical system | 12 volt - DC              |
| Battery           | 12 volt, 12 Ah            |
| Head lamp         | 12V, 60 W / 55 W, HALOGEN |
| Tail lamp         | 12V, P21/5W               |
| Turn signal lamp  | 12V, 10W X 4nos           |

**COLOURS**


Stealth black